

VACUFLEX® KA-GH PVC

Double-walled, flexible soft PVC hose

- Applications** dental technology, medical devices, cable protection
- Structure** PVC, grey / light grey (similar RAL 7035), opaque, plastic spiral / rigid PVC
- Temperature** -5°C up to 60°C
- Properties** leicht, ausgezeichnete Flexibilität, glatte Außenlage, sehr glatte Innenlage, hydrolyse- & mikrobebeständig, verrottungsfest, wetterfest



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
8	12,00	2,00	10	0,25	0,06000	2-8208-008-00
10	14,00	2,00	12	0,24	0,11800	2-8208-010-00
11	15,00	2,00	13	0,24	0,12300	2-8208-011-00
12	16,00	2,00	13	0,23	0,08500	2-8208-012-00
13	17,00	2,00	13	0,23	0,13200	2-8208-013-00
15	19,00	2,00	13	0,22	0,10600	2-8208-015-00
16	20,00	2,00	20	0,21	0,14000	2-8208-016-00
17	21,00	2,00	21	0,21	0,15000	2-8208-017-00
19	24,00	2,00	21	0,20	0,17000	2-8208-019-00
20	25,00	2,50	21	0,18	0,17900	2-8208-020-00
22	27,00	2,50	23	0,17	0,19500	2-8208-022-00
25	30,00	2,50	23	0,15	0,32900	2-8208-025-00