

APDatec 107

Flexible PVC hose reinforced with shock resistant rigid PVC spiral

Applications	agriculture, pond technology, waste water, irrigation, sewage treatment plants
Structure	PVC / soft PVC, green, transparent, plastic spiral / rigid PVC
Temperature	-5°C up to 60°C
Properties	good flexibility, high pressure resistance, high vacuum resistance, very smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
20	25,40	2,70	104	7,00	0,69	0,21000	10,50	50	1070200500
25	29,80	2,50	130	7,00	0,69	0,30000	6,25	25	1070250250
25	29,80	2,90	130	7,00	0,69	0,30000	12,50	50	1070250500
32	38,00	3,00	155	7,00	0,69	0,39000	9,75	25	1070320250
32	38,00	3,00	155	7,00	0,69	0,39000	19,50	50	1070320500
38	45,00	3,50	180	6,00	0,69	0,47000	13,00	25	1070380250
38	45,00	3,50	180	6,00	0,69	0,47000	23,50	50	1070380500
50	57,60	4,20	240	5,00	0,69	0,76000	19,00	25	1070500250
50	57,60	4,20	240	5,00	0,69	0,76000	38,00	50	1070500500